

PC-U Type Crystal Oscillator FASTXO 7.0 x 5.0 mm SMD XO Frequency up to 200MHz


FEATURE

- Typical 7.0 x 5.0 x 1.3 mm ceramic SMD package
- Operation supply voltage: 1.8V, 2.5V and 3.3V
- FASTXO series, Fast delivery at any frequency
- Tri-State Enable/Disable
- Frequency Stability ±25ppm over -40°C to 85°C
- Pb-free/RoHS compliant

TYPICAL APPLICATION

- xDSL, WLAN, Fiber/10G-bit Ethernet
- Notebook, PDA
- PC main board, VGA card


DIMENSION (mm)



Actual Size

RoHS Compliant

SOLDER PAD LAYOUT (mm)



ELECTRICAL SPECIFICATION

Parameter		3.3V		2.5V		1.8V		11
		Min.	Max.	Min.	Max.	Min.	Max.	Unit
Supply Voltage Variation		V _{DD} -5%	V _{DD} +5%	V _{DD} -5%	V _{DD} +5%	V _{DD} -5%	V _{DD} +5%	V
Frequency Range		1	200	1	200	1	125	MHz
Supply Current (@15pf Loading)		-	30	-	28	-	20	mA
Output Level	Output High	90%V _{DD}	-	90%V _{DD}	-	90%V _{DD}	-	V
	Output Low	-	10%V _{DD}	-	10%V _{DD}	-	10%V _{DD}	V
Transition Time	Rise Time / Fall Time	-	2	-	2	-	3	nSec
Duty Cycle		45	55	45	55	45	55	%
Startup Time		-	8	-	8	-	8	mSec
Tri-State mode	Output Enable	0.7 x V _{DD}	-	0.7 x V _{DD}	-	0.7 x V _{DD}	-	V
	Output Disable	-	0.3 x V _{DD}	-	0.3 x V _{DD}	-	0.3 x V _{DD}	V
Stand by Current (@PD Mode)		-	400	-	400	-	400	uA
Stand by Current (@OE Mode)		-	20	-	20	-	20	mA
Output Loading		15		15		15		pf
RMS Phase Jitter (12KHz to 20MHz) @3.3V		-	1	-	1	-	1.5	pSec
Aging (@ 25°C, First Year)		-	±3	-	±3	-	±3	ppm
Storage Temp. Range		-50	+125	-50	+125	-50	+125	°C

Standard frequencies are frequencies which the crystal has been designed and does not imply a stock position.

FREQ. STABILITY vs. TEMP. RANGE

Temp. ppm	±15	±20	±25	±50
-20~+70	Δ	0	0	0
-40~+85	×	Δ	0	0
-40~+105	X	×	Δ	0

*O: Available \triangle : Conditional X: Not available *Inclusive of calibration @ 25°C ,operating temperature rrange,ir Voltage variation,load variation,aging (1st year),shock,and vibration.

⁺ Transition times are measured between 10% and 90% of VDD, with an output load of 15pF.